AvaAluminum Lift & Slide 160

An aluminum sliding door with a thermally broken profile, 6-5/16" and 9-7/8" deep. It runs on rollers with a lift system and takes glazing up to 1-7/8" thick, for homes, shops and offices.



PERFORMANCE

Thermal insulation	**U-factor 0.21**
Sound insulation	**43 dB**
Security	**Break-in protection from multipoint locking**

TECHNICAL DATA

Profile	**Aluminum profiles with 6-5/16" and 9-7/8" construction depths, with thermal break**
Max size (2 panels)	**255-7/8" x 118-1/8"**
Max glazed area (2 panels)	**108 sq ft**
Glazing	**Triple glazing as standard, double optional, max 1-7/8" thick**
Sliding system	**Roller sliding system; 3-track sliding options**
Lift system	**Rollers on a lift system for added security and sealing**
Configurations	**2, 3, 4 or 6 moving panels, with square or rounded panel styling**
Glazing bead	**Aluminum**
Locking	**Multipoint locking, break-in protection**
Use	**Large openings in width and height, for homes, retail spaces and office buildings**
Warranty	**5 years**
Recyclability	**Recyclable**

OPENING TYPES

OPTIONS

- Sliding
- Lift & slide

- **Configurations**: 2, 3, 4 or 6 moving panels; square or rounded panel styling; 3-track sliding options.
- **Glass**: Double or triple glazing up to 1-7/8"; anti-burglary, tempered or frosted glass.
- **Hardware**: Handles and locking systems in a range of shapes and colors.
- **Colors**: White, matte, metallic, textured, woodgrain and two-tone finishes, plus antibacterial coating. Shown in pearl white, anthracite gray, light gray, ivory, matte black, burgundy red, gray green and pale green.
- **Security**: Multipoint locking for break-in protection; anti-burglary glass available.