AvaComfort 76 Entry Door

A uPVC entry door with a 5-chamber, 3" profile, a double threshold gasket and a reinforced frame. Three-point locking with bolts and hooks.



PERFORMANCE

Thermal insulation	**U-factor 0.17**
Sound insulation	**43 dB**
Security	**3-point locking with bolts and hooks**
Threshold sealing	**Double gasket at the threshold for thermal insulation**

TECHNICAL DATA

Profile	**uPVC profile, 5 chambers, 3" construction depth**
Max leaf size	**43-5/16" x 98-7/16"**
Glass and panels	**Wide range of glass or panels, up to 1-7/8" thick**
Decorative panel	**Up to 1-7/8" thick, with reinforcement options**
Spacer	**Glass unit spacer: aluminum or warm-edge**
Gaskets	**2+1**
Threshold	**Double gasket at the threshold**
Reinforcement	**Extra reinforcement forming a solid frame, plus corner connectors for stability**
Locking	**Multipoint hardware, bolts and hooks at 3 points**

Hinges	**Matching hinges, 3D or concealed hinges available**
Opening	**Inward or outward**
Warranty	**5 years**
Recyclability	**Recyclable**

OPENING TYPES

- Inward opening
- Outward opening
- Single leaf
- Multi-leaf

OPTIONS

- **Configurations**: Single-leaf or multi-leaf doors, with transoms or side panels, or even arched.
- **Glass**: Burglar-resistant glass, tempered safety glass, and a range of frosted and decorative glass.
- **Glass and panel thickness**: Glass or panels up to 1-7/8" thick, ornamental panels with reinforcement options.
- **Spacer**: Aluminum or warm-edge spacer.
- **Design**: Muntins set horizontally, vertically, diagonally or curved, or decorative uPVC panels.
- **Hardware**: Hardware in various shapes and colors, matching handles and hinges, 3D or concealed hinges.
- **Colors**: White, woodgrain finishes, matte, metallic or two-tone colors. Samples shown: Anteak, Anthracite Gray, Gray, Mahogany, Walnut, Golden Oak, Natural Oak, Light Sheffield Oak.